

**Autonics**

SP

**FUENTES CONMUTADAS****MONTAJE EN RIEL****PROTECCIÓN POR SOBRE CARGA**

| REF            | ALIMENTACIÓN | SALIDA | POTENCIA | CORRIENTE |
|----------------|--------------|--------|----------|-----------|
| <b>SP-0312</b> | 100 - 240VAC | 12VDC  | 3W       | 0.25A     |
| <b>SP-0324</b> |              | 24VDC  |          | 0.13A     |

**EBCHQ****PROTECCIÓN POR SOBRE CARGA Y CORTO CIRCUITO | CON DISPLAY**

| REF           | ALIMENTACIÓN             | SALIDA | POTENCIA | CORRIENTE |
|---------------|--------------------------|--------|----------|-----------|
| <b>43085*</b> | 90 - 240VAC              | 5VDC   | 20W      | 4A        |
| <b>43087*</b> | 127 - 380VDC             |        | 30W      | 6A        |
| <b>43000*</b> | 100 - 240VAC             | 12VDC  | 25W      | 2.1A      |
| <b>43003</b>  |                          |        | 50W      | 4.2A      |
| <b>43006</b>  | 110 - 120 / 200 - 240VAC | 24VDC  | 100W     | 8.3A      |
| <b>43020*</b> | 100 - 240VAC             |        | 25W      | 1.4A      |
| <b>43023</b>  |                          |        | 50W      | 2.1A      |
| <b>43026</b>  | 110 - 120 / 200 - 240VAC |        | 100W     | 4.2A      |
| <b>43029</b>  |                          | 300W   | 12.5A    |           |
| <b>43050*</b> | 100 - 240VAC             | 12VDC  | 24W      | 2A        |
| <b>43053*</b> |                          |        | 45W      | 3.75A     |
| <b>43059</b>  |                          | 24VDC  | 150W     | 12.5A     |
| <b>43070*</b> |                          |        | 24W      | 1A        |
| <b>43076</b>  | 24VDC                    | 72W    | 3A       |           |
| <b>43079</b>  |                          | 120W   | 5A       |           |

\*Modelos no cuentan con display

**Autonics**

SPA CE

**FUENTES CONMUTADAS****SOBREPONER****PROTECCIÓN POR SOBRE CARGA Y CORTO CIRCUITO**

| REF               | ALIMENTACIÓN | SALIDA | POTENCIA | CORRIENTE |
|-------------------|--------------|--------|----------|-----------|
| <b>SPA-030-12</b> | 100 - 240VAC | 12VDC  | 30W      | 2.5A      |
| <b>SPA-030-24</b> |              | 24VDC  |          | 1.5A      |

**EBCHQ**

| REF           | ALIMENTACIÓN                                 | SALIDA | POTENCIA | CORRIENTE |
|---------------|--|--------|----------|-----------|
| <b>43360</b>  | 110 - 240VAC ± 10%<br>(selección por switch) | 12VDC  | 36W      | 3A        |
| <b>43364</b>  |  |        | 60W      | 5A        |
| <b>43367</b>  |  |        | 100W     | 8.4A      |
| <b>43369</b>  |  |        | 150W     | 12.5A     |
| <b>43371*</b> |  |        | 250W     | 20.8A     |
| <b>43373*</b> |  |        | 348W     | 29A       |
| <b>43376</b>  |  | 24VDC  | 36W      | 1.5A      |
| <b>43378</b>  |  |        | 60W      | 2.5A      |
| <b>43380</b>  |  |        | 100W     | 4.5A      |
| <b>43382</b>  |  |        | 150W     | 6.5A      |
| <b>43384*</b> |  |        | 250W     | 10.4A     |
| <b>43386*</b> |  |        | 350W     | 14.6A     |

\*Ventilador incorporado controlado por temperatura. Salida se inactiva para temperaturas &gt; 80°C

**EBCHQ**

43397

**SOportes PARA MONTAJE EN RIEL DIN 10 X 3.5cm**

|              |        |
|--------------|--------|
| <b>43397</b> | Tipo L |
|--------------|--------|